

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product names : **Vitrified Clay Pipe: All Sizes and Styles**
Product codes : Not available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Building and Construction

1.3. Details of the supplier of the safety data sheet

Gladding, McBean
601 7th Street
Lincoln, CA 95648
T: 916 645 3341

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

The classification given below pertains to the finished product during installation when it is cut or sawn.

GHS-US classification

Skin Irritation 2
Eye Irritation 2A
Skin Sensitization 1B
Carcinogenicity 1A
Specific target organ Toxicity – Single exposure 3
Specific target Organ Toxicity - Repeated Exposure 1

2.2. Label elements**GHS-US labelling**

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS US)

6 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

Gladding, McBean: Vitrified Clay Pipe

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kaolin	(CAS No) 1332-58-7	60 - 100	Not classified
Manganese dioxide	(CAS No) 1313-13-9	≤ 5	Acute Tox. 4 (Oral) Acute Tox. 4 (Inhalation) STOT RE 2
Barium carbonate	(CAS No) 513-77-9	≤ 1	Acute Tox. 4 (Oral)
Quartz	(CAS No) 14808-60-7	≤ 1	Carc. 1A ¹ STOT RE 1 ¹
Residues, petroleum, vacuum	(CAS No) 64741-56-6	≤ 1	Not classified

¹ Only applies to airborne particles of respirable size.

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: Not a normal route of exposure. If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Dust may cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

Gladding, McBean: Vitrified Clay Pipe

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

For containment : Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Use wet methods, if appropriate, to reduce the generation of dust. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for Safe handling : When using this product, dust containing respirable silica may be generated when cutting, grinding or sawing pieces. Follow all best practices to reduce exposure to respirable silica. OSHA publishes guidelines describing these best practices, one of which is <https://www.osha.gov/Publications/OSHA3902.pdf>.

: This product is suitable for installation in exterior and interior applications.

: Avoid contact with skin and eyes. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. Use wet methods, if appropriate, to reduce the generation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle with care. When using do not eat, drink or smoke.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Kaolin (1332-58-7)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Cured Epoxy Adhesive and Urethane (Not Defined)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Barium carbonate (513-77-9)		
ACGIH	Not applicable	
OSHA	Not applicable	

Gladding, McBean: Vitrified Clay Pipe

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Residues, petroleum, vacuum (64741-56-6)

ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.
Hand protection	: Wear suitable gloves.
Eye protection	: Wear eye protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Understand and follow the requirements described in OSHA's respirable Crystalline Silica Standard, 29 CFR § 1926.1153. : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Red / Brown Fired Ceramic Product
Color	: Various
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available.

Gladding, McBean: Vitrified Clay Pipe

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

Gladding, McBean: Vitrified Clay Pipe	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5 mg/l/4h

Barium carbonate (513-77-9)	
LD50 oral rat	418 mg/kg

Residues, petroleum, vacuum (64741-56-6)	
LD50 oral rat	4320 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Based on available data, the classification criteria are not met.
Serious eye damage/irritation : Causes serious eye irritation from dust generated when cutting or sawing.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Based on available data, the classification criteria are not met.
Carcinogenicity : May cause cancer. Cutting, crushing or grinding product will release respirable crystalline silica.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans (airborne particles of respirable size)
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens (airborne particles of respirable size)

Reproductive toxicity : Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Aspiration hazard : Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation : Dust may cause respiratory tract irritation.
Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skin contact.
Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion : Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.

Gladding, McBean: Vitrified Clay Pipe

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological consideration when used according to directions.

12.2. Persistence and degradability

Gladding McBean: Vitrified Clay Pipe

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Gladding McBean: Vitrified Clay Pipe

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not regulated for transport.

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information


15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

Gladding McBean: Vitrified Clay Pipe

State or Local Regulations

 **WARNING:** This product can expose you to chemicals including Silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer, and Lead which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

SECTION 16: Other information

Date of issue : 04/22/2015

Revisions : 03/25/2019 V1.1 OSHA Silica PEL (Section 8.1) and Section 15.2 changed.
: 01/22/2020 V1.2 Classification information added to Section 2.1.
: 01/22/2020 V1.2 Additional precautions for safe handling added to Section 7.1.
: 02/06/2020 V1.3 Information about the OSHA Respirable Crystalline Silica Standard in Section 8.2 and The P65 warning at section 15.2 added.
: 03/30/2020 V1.4 Section 3.2 revised. Petroleum Distillate added.
: 05/28/2026 V1.5 P65 Warning Updated.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.